# NSN 5935-01-033-5829

Cadmium

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-5829

Body Style:
Straight shape
Overall Length:
2.729 inches
Overall Height:
0.707 inches
Overall Width:
0.494 inches
Environmental Protection:
Corrosion resistant and moisture proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
2.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Metal
Shell Surface Treatment:

## NSN 5935-01-033-5829

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

37 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.037 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.