## NSN 5935-01-033-5833

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-5833

Thread Class:
2a and 2b and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.190 inches
Overall Height:
0.500 inches
Overall Width:
1.160 inches
Environmental Protection:
Pressure proof and thermal shock resistant and vibration resistant
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.870 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.187 inches and 0.187 inches and 0.187 inches
Thready Qty Per Inch (tpi):
56 and 56 and 40
Thread Size:
0.086 inches and 0.086 inches and 0.112 inches

Terrinia Location

Back single mating end single contact grouping

## NSN 5935-01-033-5833

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:
Wire loop single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204 ty ii military specification single treatment response
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
4 mtg holes on a side 0.730 in. C to c
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.150 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-g-45204 spec.

Mil-std (military Standard):