Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-6550

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.780 inches
Overall Height:
0.620 inches
Overall Width:
0.280 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
0.531 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.240 inches
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-01-033-6550

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.