NSN 5935-01-033-7894

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-7894

2b
Thread Direction:
Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
1.630 inches
Overall Height:
1.040 inches
Overall Diameter:
0.590 inches
Environmental Protection:
Salt water resistant and shock proof and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
75.0 single mating end single contact grouping
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-033-7894Electrical Plug Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Shell Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold and contact @and pody surface silver
Precious Material And Weight:
0.105 gold grains, troy and 0.105 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0