

View Online at <https://aerobasegroup.com/nsn/5935-01-033-9105>

Body Style:

Straight shape w/clamp

Environmental Protection:

Shock resistant

Cable Entrance Diameter:

Between 0.380 inches and 0.755 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

18-50 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

208.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

208.0 single mating end single contact grouping

Polarization Method:

Contact

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Screw single mating end single contact grouping

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Test Data Document:

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-81348-wc596-29 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0