

View Online at <https://aerobasegroup.com/nsn/5935-01-033-9106>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external/internal coupling

Overall Length:

Between 1.927 inches and 1.937 inches

Overall Diameter:

0.688 inches

Environmental Protection:

Moisture resistant and vibration resistant and corrosion resistant and shock proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.625 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.