NSN 5935-01-033-9116

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-9116 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 2.750 inches **Overall Height:** 1.350 inches **Overall Width:** 2.420 inches **Environmental Protection:** Vibration resistant and shock proof **Unthreaded Mounting Hole Diameter:** 0.149 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.045 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 80 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type: **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 28

Thread Size: 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

NSN 5935-01-033-9116

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Stainless steel **Included Contact Quantity:** 80 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.080 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: