# NSN 5935-01-034-0315

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-034-0315 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.486 inches and 1.551 inches **Overall Height:** Between 1.695 inches and 1.711 inches **Overall Width:** Between 1.695 inches and 1.711 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 1.370 inches and 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** Between 0.894 inches and 0.906 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 50.0 and 160.0 and 190.0 and 225.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28

**Thread Size:** 

1.500 inches

# NSN 5935-01-034-0315

Electrical Receptacle Connector - Page 2 of 3



Term	inal	Location:
16111	IIIIai	LUCALIUII.

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy 6061

#### **Shell Surface Treatment:**

Cadmium

#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Shell Material Specification:**

Qq-a-367 comp 6061, t6 federal specification single material response

#### **Included Contact Quantity:**

41 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

# **Special Features:**

Contact designation 24-41

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.041 gold grains, troy

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Un

#### **Specification Data:**

81349-mil-c-81511-21 government specification

#### **Shelf Life:**

N/a

# **Unit Of Measure:**

#### Demilitarization:

No

# Fiig:

•

# NSN 5935-01-034-0315

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.