NSN 5935-01-034-1844

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-034-1844 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.375 inches **Overall Diameter:** 1.750 inches **Environmental Protection:** Corrosion resistant and waterproof and watertight **Distance From Mounting Shoulder To Front Face:** 0.863 inches **Mounting Facility Thickness:** Between 0.060 inches and 0.250 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 6-dec single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-034-1844

Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Solder well single mating end single contact grouping **Included Contact Quantity:** 6 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Solder flange mtg **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.006 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A039b0