## NSN 5935-01-034-1847

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-034-1847

**Body Style:** 

Straight type

**Overall Length:** 

Between 5.615 inches and 5.625 inches

**Overall Height:** 

Between 0.645 inches and 0.655 inches

**Overall Width:** 

Between 0.369 inches and 0.379 inches

**Environmental Protection:** 

Humidity resistant and shock proof and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.128 inches and 0.132 inches

**Distance Between Mounting Facility Centers:** 

Between 5.357 inches and 5.367 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1250.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

## NSN 5935-01-034-1847

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 47 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Polarizing positions all except c and d **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.047 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.