NSN 5935-01-034-1848



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-034-1848 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.173 inches **Overall Height:** 1.350 inches **Overall Width:** 2.875 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 104 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping **Insert Material:**

Plastic diallyl phthalate single mating end

NSN 5935-01-034-1848

Electrical Receptacle Connector - Page 2 of 2



T	erm	inal	Typ	e:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Polarized at position 2 n

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.