NSN 5935-01-034-2603

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-034-2603
Body Style:
Straight shape, external coupling
Overall Length:
0.697 inches
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
Between 0.442 inches and 0.447 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Shell Material: Aluminum alloy

Cadmium

Included Contact Quantity:

79 single mating end all contact groupings

NSN 5935-01-034-2603

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end all contact groupings

Test Data Document:

Shelf Life:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Mil-c-38999 spec.

A039b0