

View Online at <https://aerobasegroup.com/nsn/5935-01-034-4858>

Body Style:

Straight shape, internal coupling

Overall Length:

1.400 inches

Overall Diameter:

0.562 inches

Environmental Protection:

Moisture resistant and vibration resistant and corrosion resistant and shock proof

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 2nd mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

335.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

4000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and externally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Material:

Copper alloy 1st mating end all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Qq-c-530 federal specification single material response 1st mating end all contact groupings and qq-b-626, alloy 360, 1/2 h federal specification single material response 1st mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Insert Material Specification:

L-p-403, type 1 federal specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 1st mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0