

View Online at <https://aerobasegroup.com/nsn/5935-01-034-4858>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.400 inches

**Overall Diameter:**

0.562 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and corrosion resistant and shock proof

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 2nd mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 all mating ends all contact groupings

**Contact Maximum Frequency Rating:**

4000.0 megahertz all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin and externally threaded coupling nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Contact Material:**

Copper alloy 1st mating end all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-c-530 federal specification single material response 1st mating end all contact groupings and qq-b-626, alloy 360, 1/2 h federal specification single material response 1st mating end all contact groupings

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Insert Material Specification:**

L-p-403, type 1 federal specification single material response all mating ends

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial socket 1st mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0