

View Online at <https://aerobasegroup.com/nsn/5935-01-034-8078>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.875 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Vibration resistant and humidity resistant and shock proof and salt water resistant

Distance From Mounting Shoulder To Front Face:

0.575 inches

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36 and 36

Thread Size:

0.250 inches and 0.250 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Insert Material:

Rubber all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response all mating ends single contact grouping

Shell Material:

Steel comp 303

Shell Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

Included Contact Quantity:

2 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.