

View Online at <https://aerobasegroup.com/nsn/5935-01-035-3630>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.000 inches

**Overall Height:**

0.530 inches

**Overall Width:**

0.340 inches

**Distance Between Mounting Facility Centers:**

0.750 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

56 and 56 and 56

**Thread Size:**

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material And Weight:**

0.014 gold grains, troy and 0.014 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19833 spec.