NSN 5935-01-035-3631

36 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-035-3631

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length:
2.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches
Overall Height:
2.000 inches
Overall Width:
0.830 inches
Environmental Protection:
Moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.149 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Polarization boss
Connector Locking Method:
Screw lock pin
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14 type sdg-f military specification single material response single mating end or mil-m-19833 type gdi-30f military specification single
material response single mating end
Included Contact Quantity:

NSN 5935-01-035-3631

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Polarized at position 1 n
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-28748/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.