Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-035-5659

# Body Style:

Straight shape, external coupling

### **Overall Length:**

1.100 inches

## **Overall Height:**

Between 1.338 inches and 1.348 inches

#### **Overall Width:**

Between 1.338 inches and 1.348 inches

#### **Environmental Protection:**

Corrosion resistant and dust resistant and shock resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.116 inches and 0.125 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.057 inches and 1.067 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.057 inches and 1.067 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

18-31 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Glass fiber single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Stainless steel



**Included Contact Quantity:** 31 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.031 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0