Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-035-7653

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| Between 1.172 inches and 1.222 inches |
| Overall Height: |
| Between 1.335 inches and 1.351 inches |
| Overall Width: |
| Between 1.335 inches and 1.351 inches |
| Environmental Protection: |
| Moisture resistant and pressure proof and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.121 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 1.057 inches and 1.067 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 1.057 inches and 1.067 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.765 inches and 0.775 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 18-09 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thready Qty Per Inch (tpi): |
| |
| Thread Size: |
| 1.125 inches |
| |



| Torminal Location. |
|---|
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Chromium |
| Shell Material Specification: |
| Qq-a-367, comp t6 federal specification single material response |
| Included Contact Quantity: |
| 9 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.009 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |
| |