## NSN 5935-01-036-0943

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-036-0943

**Body Style:** 

Straight shape, external coupling

**Bushing Diameter:** 

0.453 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.531 inches

**Mating End Quantity:** 

.

**Contact Position Arrangement Style:** 

Bnc single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic tetrafluoroethylene single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Copper alloy

**Shell Material Specification:** 

Qq-b-626 federal specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

## NSN 5935-01-036-0943

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0