

View Online at <https://aerobasegroup.com/nsn/5935-01-036-3606>

Body Style:

Straight shape, external coupling w/backshell

Overall Height:

1.703 inches

Overall Width:

1.703 inches

Environmental Protection:

Moisture resistant and weatherproof and weather resistant

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.152 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Distance From Mounting Shoulder To Front Face:

Between 0.673 inches and 0.693 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

2100.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0