NSN 5935-01-036-5169

Thread Class: 2a and 2a

Body Style:

Overall Length: 0.641 inches Overall Height:

Thread Direction:

Right-hand and right-hand

Angle shape, external coupling

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-036-5169

0.719 inches
Overall Diameter:
0.273 inches
Distance From Mounting Shoulder To Front Face:
0.438 inches
Mounting Facility Thickness:
0.094 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32 and 32
Thread Size:
0.190 inches and 0.190 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-01-036-5169

Electrical Receptacle Connector - Page 2 of 2



insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and silver
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact and body surface gold and contact and body surface silver
Precious Material And Weight:
0.105 gold grains, troy and 0.105 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unf and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0