

View Online at <https://aerobasegroup.com/nsn/5935-01-036-5576>

Body Style:

Straight shape, external coupling

Overall Length:

0.699 inches

Overall Height:

1.219 inches

Overall Width:

1.219 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

Distance From Mounting Shoulder To Front Face:

0.317 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

16-26 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

600.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

50.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.026 gold grains, troy and 0.026 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0