NSN 5935-01-037-6161

Unthreaded Mounting Hole Diameter:

Body Style:
Straight type
Overall Length:
7.150 inches
Overall Height:
0.565 inches
Overall Width:
0.250 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-037-6161

0.120 inches
Distance Between Mounting Facility Centers:
6.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic phenolic single mating end and glass single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Wire wrap single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Included Contact Quantity:
120 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Left side d-shaped pin guide rotated at 90 deg, right side d-shaped socket guide rotated at 270 degrees clockwise from normal

NSN 5935-01-037-6161

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.120 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.