Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-037-6171

Body Style:
Straight type
Overall Length:
5.625 inches
Overall Height:
0.650 inches
Overall Width:
0.374 inches
Unthreaded Mounting Hole Diameter:
0.130 inches
Distance Between Mounting Facility Centers:
5.362 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Polarization Method:
Shell
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, cl i, grade c military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
On b 626 federal aposition single material response single mating and single contact grouping

Qq-b-626 federal specification single material response single mating end single contact grouping



Insert Material Specification: Mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 47 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Polarized in positions b, c, d, e, f, g, h, andk **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.047 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.