## NSN 5935-01-037-6188

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-037-6188

**Body Style:** 

Straight edge type

**Overall Length:** 

**4.750** inches

**Overall Width:** 

0.453 inches

**Environmental Protection:** 

Moisture resistant

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

4.280 inches

**Board Accommodated Length:** 

4.200 inches single board

**Board Accommodated Width:** 

0.074 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

1 row of contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

10.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

20 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

## NSN 5935-01-037-6188

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.