

View Online at <https://aerobasegroup.com/nsn/5935-01-037-6634>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external/internal coupling

Overall Diameter:

0.250 inches

Environmental Protection:

Moisture resistant and vibration resistant and shock proof and thermal shock resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Detent and externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic melamine all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

Insert Material Specification:

Mil-p-19466 military specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.