Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-038-1575

# Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

# Body Style:

Hood, side opening w/clamp

## **Overall Length:**

3.230 inches

#### **Overall Height:**

2.467 inches

# **Overall Width:**

1.188 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant

#### Cable Entrance Diameter:

0.550 inches

## Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

75 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

## **Polarization Method:**

Jackscrew

## Shell Type:

Hood, side opening

## **Connector Locking Method:**

Jackscrew-socket

## Connector Cable Strain Relief Method:

Cable clamp

#### **Thread Length:**

0.320 inches

# Thread Size:

0.138 inches and 0.138 inches

## **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# NSN 5935-01-038-1575

Electrical Plug Connector - Page 2 of 2



#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# **Included Contact Quantity:**

75 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.075 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unc and unc

# **Specification Data:**

81349-mil-c-28748/4 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

```
Fiig:
```

A039b0