NSN 5935-01-038-1576

Thread Class: 2a and 2b

Body Style:

Overall Length: 2.835 inches Overall Height:

Thread Direction:

Right-hand and right-hand

Hood, top opening w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-038-1576

| Overall neight. | |
|---|---------------|
| 3.282 inches | |
| Overall Width: | |
| 1.625 inches | |
| Environmental Protection: | |
| Moisture resistant and vibration resistant | 1 |
| Cable Entrance Diameter: | |
| 1.100 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 25-104 single mating end | |
| Contact Removability: | |
| Removable single mating end single con | tact grouping |
| Contact Maximum Current Rating In A | mps: |
| 7.5 single mating end single contact grou | uping |
| Polarization Method: | |
| Jackscrew | |
| Shell Type: | |
| Hood, top opening | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Connector Cable Strain Relief Method | : |
| Cable clamp | |
| Thread Length: | |
| 0.375 inches and 0.320 inches | |
| Thread Size: | |
| 0.164 inches and 0.164 inches | |
| Terminal Location: | |
| Back single mating end single contact gr | ouping |
| Contact Surface Treatment: | |
| Gold single mating end single contact great | ouping |
| | |

NSN 5935-01-038-1576Electrical Plug Connector - Page 2 of 2



| Insert Material: |
|--|
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 104 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.104 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unc and unc |
| Specification Data: |
| 81349-mil-c-28748/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |