

NSN 5935-01-038-1587 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-038-1587 **Thread Class:** За **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.435 inches **Overall Height:** 0.521 inches **Overall Width:** 0.258 inches **Environmental Protection:** Shock proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.089 inches and 0.094 inches **Distance Between Mounting Facility Centers:** Between 1.215 inches and 1.220 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 51 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end all contact groupings

NSN 5935-01-038-1587

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity: |
|--|
| 41 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round socket single mating end all contact groupings |
| Special Features: |
| 15.00 in. Wire lead terminals |
| Precious Material And Location: |
| Contacts @surfaces gold |
| Precious Material And Weight: |
| 0.051 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A039b0