

NSN 5935-01-038-1587 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-038-1587 **Thread Class:** За **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.435 inches **Overall Height:** 0.521 inches **Overall Width:** 0.258 inches **Environmental Protection:** Shock proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.089 inches and 0.094 inches **Distance Between Mounting Facility Centers:** Between 1.215 inches and 1.220 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 51 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end all contact groupings

NSN 5935-01-038-1587

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
41 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
15.00 in. Wire lead terminals
Precious Material And Location:
Contacts @surfaces gold
Precious Material And Weight:
0.051 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0