NSN 5935-01-038-6497

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-038-6497

Body Style: Straight shape, flush mount **Overall Length:** 0.954 inches **Overall Height:** 3.110 inches **Overall Width:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.437 inches **Distance From Mounting Shoulder To Front Face:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 67 1st mating end **Contact Removability:** Removable all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back all mating ends single contact grouping **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic diallyl phthalate all mating ends **Contact Surface Treatment Specification:** Mil-g-45204, type 1, class 1 military specification single treatment response all mating ends single contact grouping **Terminal Type:** Crimp all mating ends single contact grouping **Shell Material:** Aluminum alloy 380.0 **Shell Surface Treatment:** Cadmium

Caamiam

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5935-01-038-6497

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Qq-a-591, alloy 380 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response all mating ends

Included Contact Type:

Round socket all mating ends single contact grouping

Special Features:

Polarized in position 27

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.134 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.