Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-038-8740



Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

2.500 inches

Overall Height:

1.567 inches

Overall Diameter:

0.875 inches

Environmental Protection:

Shock proof and vibration resistant

Cable Entrance Diameter:

0.382 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Hn single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Wedge-lock

Radio Frequency Type Contact Characteristic Impedance In Ohms:

500.0 single mating end single contact grouping

Thread Size:

0.625 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-01-038-8740

Electrical Plug Connector - Page 2 of 2



Insert Material: Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626 federal specification single material response single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Silver **Shell Surface Treatment Specification:** Qq-s-365, type 2 federal specification single treatment response **Shell Material Specification:** Qq-b-626 federal specification single material response **Insert Material Specification:** Mil-p-19468 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and body surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19468 spec.