Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-039-3119

### **Body Style:**

Straight edge type w/card guide

### **Overall Length:**

Between 5.240 inches and 5.260 inches

## **Overall Width:**

0.372 inches

**Body Height:** 

0.460 inches

#### **Environmental Protection:**

Humidity resistant and shock proof and vibration resistant and salt water resistant

#### **Board Accommodated Length:**

5.125 inches single board

#### **Board Accommodated Width:**

Between 0.071 inches and 0.077 inches

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

### Contact Removability:

Removable single mating end 1st contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end 1st contact grouping

### Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Glass single mating end and plastic polyamide single mating end

## **Terminal Type:**

Wire wrap single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end 1st contact grouping

## Included Contact Quantity:

9 single mating end single contact grouping

## **Special Features:**

Printed circuit mtd

## **Precious Material And Location:**

Contact surfaces gold



**Precious Material And Weight:** 

0.009 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0