

View Online at <https://aerobasegroup.com/nsn/5935-01-040-1265>

Body Style:

Straight shape w/clamp

Overall Height:

2.750 inches

Overall Diameter:

1.550 inches

Cable Entrance Diameter:

Between 0.325 inches and 0.615 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

130-2-iec-18 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Cable Strain Relief Method:

Crimp type

End Application:

Missile minuteman Igm-30

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

1 single mating end 3rd contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/42 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0