

View Online at <https://aerobasegroup.com/nsn/5935-01-040-1284>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.125 inches

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.781 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20-27 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded coupling ring

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.875 inches and 1.250 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic silicone mineral filled single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-c-5015 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0