NSN 5935-01-040-4071

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-4071 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** 1.875 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 1.156 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.297 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-22 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 73.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 18

Thread Size:

1.375 inches and 1.375 inches

NSN 5935-01-040-4071

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0