Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-4072

Thread Class:	
2a	
Za Thread Direction:	
Right-hand	
Body Style:	lin e
Straight shape, external coup	ling
Overall Length:	
Between 1.461 inches and 1.6	SUT Inches
Overall Height:	
2.750 inches	
Overall Width:	
2.750 inches	
Unthreaded Mounting Hole	
Between 0.171 inches and 0.7	
	Between Mounting Facilities Parallel To Height:
2.188 inches	
	es Of Mounting Facilities Parallel To Body Width:
2.188 inches	
Distance From Mounting Sh	oulder To Front Face:
Between 0.875 inches and 0.8	385 inches
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangeme	ent Style:
40-62 single mating end	
Contact Removability:	
Removable single mating end	single contact grouping
Contact Maximum Current F	Rating In Amps:
22.0 single mating end single	contact grouping
Contact Maximum Ac Voltag	ge Rating In Volts:
660.0 single mating end single	e contact grouping
Contact Maximum Dc Voltag	ge Rating In Volts:
940.0 single mating end single	e contact grouping
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	:
Externally threaded shell	

Electrical Receptacle Connector - Page 2 of 2



Thread Length: 0.625 inches Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.200 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 60 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.060 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-r-3065 spec.