

NSN 5935-01-040-6071 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-040-6071 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.248 inches **Overall Diameter:** 2.312 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.915 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 25-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-01-040-6071

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium and chromate	
Included Contact Quantity:	
100 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surface gold and contact surface silver	
Precious Material And Weight:	
0.100 gold grains, troy and 0.100 silver grains, troy	
Precious Material:	
Gold and silver	
Test Data Document:	
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification	n type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general	I type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "",	etc.).
Thread Series Designator:	
Uns	
Specification Data:	
81349-mil-c-38999 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	