NSN 5935-01-040-6250

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-6250 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** Between 1.275 inches and 1.340 inches **Overall Height:** Between 0.804 inches and 0.820 inches **Overall Width:** Between 0.804 inches and 0.820 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.589 inches and 0.599 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.589 inches and 0.599 inches **Distance From Mounting Shoulder To Front Face:** Between 0.765 inches and 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 40394 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 296.0 and 205.0 and 126.0 and 56.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches

0.500 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-040-6250

Electrical Receptacle Connector - Page 2 of 2



_							
r -	n	+-	rt.	NЛ	ate	rio	
·	OI.	ιca	·ι	IVI	alc	на	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-367, t6 federal specification single material response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-81511/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.