NSN 5935-01-040-6730

Plug-in Electronic Components Socket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-040-6730 |
|--|
| Body Material: |
| Plastic |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Top mount w/studs |
| Overall Length: |
| 1.438 inches |
| Overall Height: |
| 0.812 inches |
| Overall Width: |
| 0.609 inches |
| Mounting Hole Diameter: |
| 0.234 inches |
| Mounting Hole Style: |
| Four mounting holes/slots |
| Contact Maximum Current Rating In Amps: |
| 3.0 |
| Contact Material: |
| Phosphor bronze |
| Contact Surface Treatment: |
| Gold and nickel |
| Accommodated Contact Quantity: |
| 14 |
| Center To Center Distance Between Outside Mounting Holes Along Length: |
| 1.200 inches |
| Center To Center Distance Between Outside Mounting Holes Along Width: |
| 0.400 inches |
| Polarization Type: |
| Contact position |
| Projection Length Below Mounting Surface: |
| 0.485 inches |
| Mounting Method: |
| Threaded stud |
| Mounting Type For Which Designed: |
| Chassis |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |

0.112 inches

NSN 5935-01-040-6730

Plug-in Electronic Components Socket - Page 2 of 2



| Contact Position Arrangement Style: |
|--|
| Symmetrical |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.014 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 14 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A02300 |