Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-7510

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.531 inches
Overall Diameter:
Between 2.230 inches and 2.260 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
1.219 inches
Mounting Facility Thickness:
0.298 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
24-22 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
73.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
940.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1300.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
45.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.500 inches and 1.500 inches



**Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Included Contact Quantity:** 4 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0