NSN 5935-01-040-7515



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-040-7515 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** Between 3.105 inches and 3.135 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 1.250 inches **Mounting Facility Thickness:** 0.298 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 36-10 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 660.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 940.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Thready Qty Per Inch (tpi):

16 and 16

Thread Size:

2.250 inches and 2.250 inches

NSN 5935-01-040-7515

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
48 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.048 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0