## NSN 5935-01-040-7999

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-7999 **Thread Class: Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.890 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.968 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.968 inches **Distance From Mounting Shoulder To Front Face:** 0.312 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 27 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Spring friction

Thread Size: 0.086 inches

## NSN 5935-01-040-7999

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
8 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-mil-m-14 spec.