# NSN 5935-01-040-8010

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-040-8010

## **Body Style:**

Straight shape, external coupling w/backshell

## **Overall Length:**

0.692 inches

# **Overall Height:**

1.234 inches

# **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.317 inches and 0.322 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

16-6 single mating end

## Contact Removability:

Removable single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Cadmium and chromate   |
| Included Contact Quantity:   |
| 6 single mating end single contact grouping  |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold and contact surfaces silver  |
| Precious Material And Weight:  |
| 0.030 gold grains, troy and 0.030 silver grains, troy  |
| Precious Material:   |
| Gold and silver  |
| Test Data Document:  |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
|  |