Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-041-1351

| View Online at https://aerobasegroup.com/nsn/5935-01-041-1351 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.085 inches |
| Overall Width: |
| 0.250 inches |
| Environmental Protection: |
| Moisture resistant and shock proof and vibration resistant and salt water resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Distance Between Mounting Facility Centers: |
| 0.865 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 21 single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end all contact groupings |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Wire wrap single mating end 2nd contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 6 single mating end 1st contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces gold |
| |



Precious Material And Weight:

0.021 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0