# NSN 5935-01-041-2019

Electrical Receptacle Connector - Page 1 of 2



Body Style: Straight shape, external coupling Overall Length: 1.275 inches Overall Height: 1.578 inches Overall Width: 1.578 inches Unthreaded Mounting Hole Diameter:					
Overall Length: 1.275 inches Overall Height: 1.578 inches Overall Width: 1.578 inches					
1.275 inches  Overall Height: 1.578 inches  Overall Width: 1.578 inches					
Overall Height: 1.578 inches Overall Width: 1.578 inches					
1.578 inches  Overall Width:  1.578 inches					
Overall Width: 1.578 inches					
1.578 inches					
Unthreaded Mounting Hole Diameter:					
Unthreaded Mounting Hole Diameter:					
0.120 inches					
Center To Center Distance Between Mounting Facilities Parallel To Height:					
1.250 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:					
1.250 inches					
Distance From Mounting Shoulder To Front Face:					
0.641 inches					
Mating End Quantity:					
1					
Contact Position Arrangement Style:					
22-41 single mating end					
Contact Removability:					
Removable single mating end all contact groupings					
Polarization Method:					
Keyway or multiple keyway					
Insert Position In Deg:					
264.0					
Shell Type:					
Solid					
Connector Locking Method:					
Bayonet pin					
Terminal Location:					
Back single mating end all contact groupings					
Terminal Type:					
Crimp and solder single mating end all contact groupings					

#### **Shell Material:**

Aluminum alloy 6061

## **Shell Material Specification:**

Qq-a-367, comp 6061, t6 federal specification single material response

## **Included Contact Quantity:**

27 single mating end 2nd contact grouping

## **Included Contact Type:**

Round pin single mating end all contact groupings

## NSN 5935-01-041-2019

Electrical Receptacle Connector - Page 2 of 2



#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

		ife	

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.