

View Online at <https://aerobasegroup.com/nsn/5935-01-041-2700>

Body Style:

Straight shape, rectangular

Overall Length:

3.969 inches

Overall Height:

0.968 inches

Overall Width:

1.250 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

3.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

32 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Shell

Shell Type:

Solid

Connector Locking Method:

Lever-pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Shell Guide Type And Location Designator:

A slot and c slot and 3 slot and 6 slot

Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.