## NSN 5935-01-041-2884

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-041-2884

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
5.781 inches
Overall Diameter:
Between 1.438 inches and 1.500 inches
Environmental Protection:
Corrosion resistant and moisture proof and vibration resistant
Cable Entrance Diameter:
Between 0.438 inches and 0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-1 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thread Length:
0.390 inches and 0.422 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping

## NSN 5935-01-041-2884

Electrical Plug Connector - Page 2 of 2



## **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 11, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Mil-c-14550 class 4 military specification single material response single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 11, class 3 federal specification single treatment response **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-c-14550 spec.