NSN 5935-01-041-2911

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-041-2911

Thread Class.
Thread Class:
2a Three d Directions
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.100 inches
Overall Diameter:
1.475 inches
Environmental Protection:
Corrosion resistant and moisture resistant and shock proof and thermal shock resistant and salt water resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-37 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
28
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-041-2911Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-367, t6 federal specification single material response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contact designation 18-37
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.